

RP-1000

RACK & PINION MATERIAL HOIST

Small Loads & Scaffold Erection

Standard Features

- » 1,000 lb Max Load Capacity*
- » 400 ft Max Vertical Travel**
- » 90 fpm Operating Speed*
- » 31"W x 60"L x 48"H Clear Platform
- » 100% Duty Cycle
- » 220V / 1P / 60Hz / 30A*
- » Base Unit Weight: 1,300 lbs
- » Steel Construction
- » Soft-Start/Soft-Stop
Variable Frequency Drive for Smooth Acceleration and Deceleration
- » Fast Acting Overspeed Brake
- » Safety Chains on Access Sides
- » Drop-down Ramps on Access Sides
- » Extendable Pendant Control
- » Water Tight Connectors
- » 5'H Tower Sections (Stackable)
- » Anchors to Building or Scaffolding
Use standard anchorage brackets or custom made brackets every 10-15'.
- » Material Use Only

Many Options Available

* Constant voltage is required to prevent damage and to maintain specified lift capacity and speed.

** Consult a structural engineer for heights over 200 ft or when unsure of required anchoring.

Material Use Only - No Riders



Shown without optional ANSI Platform Enclosure



For more information contact us at:

1-800-451-5053

Ph: 321-733-3387 Fx: 321-733-9433

360 East Drive, Melbourne, FL 32904, USA

sales@hi-techhoist.com www.hi-techhoist.com